

PART OF THE **DURAN**® BOTTLE SYSTEM

EXTENDED

DURAN® GLS 80® BOTTLE



DWK LIFE SCIENCES
DURAN WHEATON KIMBLE

DURAN® GLS 80® LABORATORY BOTTLE WIDE MOUTH



with GLS 80® thread



With easy-to-read scale and large labelling field for easy marking, in fired-on, highly durable white ceramic. Complete with blue quick release closure (PP, integral lip seal) and pouring ring (PP) for drip-free pouring and clean, safe working. Service temperature limit of closure and pouring ring: +140 °C. Special thread means opening takes less than a turn. The 80 mm wide outer diameter of the bottle mouth permits easy filling and pouring out of powders and viscous substances.

Typical applications: storage, transport, safekeeping and sampling of substances, easy to use with granulated material, powders and viscous media, sampling of hot media.

Cat. No.	Capacity (mL)	Thread	d (OD) (mm)	h (mm)	Pack Unit
with screw cap and pouring ring from PP (blue)					
21 860 36 56	250	GLS 80®	95	110	10
11 126 27	500	GLS 80®	101	153	10
11 127 13	1 000	GLS 80®	101	223	10
11 127 15	2 000	GLS 80®	136	253	10
21 860 69 53	3 500	GLS 80®	160	276	1
11 139 49	5 000	GLS 80®	182	315	1
11 139 50	10 000	GLS 80®	227	390	1
11 139 51	20 000	GLS 80®	288	485	1
12 002 65	30 000	GLS 80®	340	548	1
12 001 54	50 000	GLS 80®	400	590	1
without screw cap and pouring ring from PP (blue), clear					
21 860 36 07	250	GLS 80®	95	105	10
11 783 92	500	GLS 80®	101	148	10
11 784 24	1 000	GLS 80®	101	218	10
11 784 25	2 000	GLS 80®	136	248	10
21 860 69 04	3 500	GLS 80®	160	271	1
11 784 26	5 000	GLS 80®	182	310	1
11 784 27	10 000	GLS 80®	227	385	1
11 784 28	20 000	GLS 80®	288	480	1




> Find your nearest **distributor** on our global network:
www.dwk.com/distributors

DURAN® GLS 80® LABORATORY BOTTLE WIDE MOUTH AMBER



with GLS 80®, USP <660> and USP <671> (Spectral Transmission) compliant



With easy-to-read scale and large labelling field for easy marking, in fired-on, highly durable white ceramic. Complete with blue quick release closure (PP, integral lip seal) and pouring ring (PP) for drip-free pouring and clean, safe working. Service temperature limit of closure and pouring ring: +140 °C. Alongside easy handling, UV protection up to 500 nm. Unchanged DURAN® properties within the bottle, as colouration is only to the outer surface. Very uniform, durable and chemically resistant amber colour due to use of innovative technology.

Typical applications: storage, transport and safekeeping of light-sensitive substances, easy to use with granulated material, powders and viscous media.


Cat. No.	Capacity (mL)	Thread	d (OD) (mm)	h (mm)	Pack Unit
with screw cap and pouring ring from PP (blue)					
21 866 36 53	250	GLS 80®	95	110	10
11 601 46	500	GLS 80®	101	153	10
11 601 47	1 000	GLS 80®	101	223	10
11 601 48	2 000	GLS 80®	136	253	10
21 866 69 59	3 500	GLS 80®	160	276	1
11 601 49	5 000	GLS 80®	182	315	1
11 601 50	10 000	GLS 80®	227	390	1
11 601 51	20 000	GLS 80®	288	485	1
without screw cap and pouring ring					
21 866 36 04	250	GLS 80®	95	105	10
11 784 29	500	GLS 80®	101	148	10
11 784 30	1 000	GLS 80®	101	218	10
11 784 31	2 000	GLS 80®	136	248	10
21 866 69 01	3 500	GLS 80®	160	271	1
11 784 32	5 000	GLS 80®	182	310	1
11 784 33	10 000	GLS 80®	227	385	1
11 784 34	20 000	GLS 80®	288	480	1



DURAN® GLS 80® PROTECT LABORATORY BOTTLE WIDE MOUTH



with GLS 80® thread, plastic coated



With easy-to-read scale. In fired-on, highly durable white ceramic. Complete with blue quick release closure (PP, integral lip seal) and pouring ring (PP) for drip-free pouring and clean, safe working. Service temperature limit of closure and pouring ring: +140 °C. Service temperature limit of the PU plastic coating: -30 °C to +135 °C. The coating provides scratch, leak and splinter protection and is ideally suited to both the transport and storage of hazardous media or valuable samples. UV protection up to approx. 380 nm wavelength. High transparency. Suitable for microwaving.


Typical applications: storage, transport and safe handling of hazardous substances. Storage of high value viscous liquids, pastes and powder.

Cat. No.	Capacity (mL)	Thread	d (OD) (mm)	h (mm)	Pack Unit
with screw cap and pouring ring from PP (blue)					
21 865 36 52	250	GLS 80®	95	110	10
11 601 52	500	GLS 80®	101	153	10
11 601 63	1 000	GLS 80®	101	223	10
11 601 64	2 000	GLS 80®	136	253	10
21 865 69 58	3 500	GLS 80®	160	276	1
11 601 65	5 000	GLS 80®	182	315	1
without screw cap and pouring ring					
21 865 36 03	250	GLS 80®	95	105	10
21 865 69 09	3 500	GLS 80®	160	271	1

DURAN® GLS 80® PROTECT LABORATORY BOTTLE WIDE MOUTH AMBER



with GLS 80® thread, plastic coated, USP <660> and USP <671> (Spectral Transmission) compliant



With easy-to-read scale and large labelling field for easy marking, in fired-on, highly durable white ceramic. Complete with blue quick release closure (PP, integral lip seal) and pouring ring (PP) for drip-free pouring and clean, safe working. Service temperature limit of closure and pouring ring: +140 °C. Service temperature limit of the PU plastic coating: -30 °C to +135 °C. The coating provides scratch, leak and splinter protection and is ideally suited to both the transport and storage of hazardous media or valuable samples. UV protection up to approx. 380 nm wavelength. Suitable for microwaving.

Typical applications: storage, transport and safe handling of hazardous substances. Storage of high value viscous liquids, pastes and powder.

Cat. No.	Capacity (mL)	Thread	d (OD) (mm)	h (mm)	Pack Unit
with screw cap and pouring ring from PP (blue)					
11 673 08	500	GLS 80®	101	153	10
11 673 09	1 000	GLS 80®	101	223	10
without screw cap and pouring ring					
21 866 44 36	500	GLS 80®	101	148	10
21 866 54 32	1 000	GLS 80®	101	218	10
21 866 63 34	2 000	GLS 80®	136	248	10
21 866 69 34	3 500	GLS 80®	160	271	1
21 866 73 39	5 000	GLS 80®	182	310	1

